

Outdoor Camera

CA60HDc



Focal length 2.8 mm

97°

Up to
8.8 meters*


Identification

Up to
15 meters*


Plate reading

Up to
18 meters*


Recognition

*Daytime distances

Data sheet

Sensor	1/3" CMOS
Resolution	2688 x 1520 pixels - 25 IPS
Focal length	2.8 mm
Angle	97°
Sensitivity Range	0,05 Lux (color), 0 Lux with IR
Infrared range by night	30 meters
Intelligence **	People detection, perimeter, single or double line crossing, added or missing object, abnormal speed, illegal parking, bad signal, motion detection, network disconnection
Images *	3D DNR, WDR, ICR, HLC, ROI, DIS, Fog lamps, Corridor mode
Video compression	H.264, H.265, MJPEG
Video flow	100kbps to 12Mbps
Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP, Vizeo
Compatibility	RTSP - ONVIF

Positioning	3 axis
Power supply and consumption	12V DC, PoE et 5 W Max.
Dimensions and weight	187 x 64 x 64 mm and 540g
Operating temperature	-30° to 50°c with 90% non-condensing humidity
Protection sign *	IP66, IK06
Guarantee	3 years

Recommended accessory



SP50HD
Junction box


* See page 3 | ** See page 4

Technical glossary

Camera performance

without

with



WDR

Avoid backlighting and loss of detail in shadow areas.



ICR

Mechanical filter that allows, during the day, a faithful reproduction of the colorimetry of the filmed images.




3D DNR

Noise reduction (spurious color dots) in dark areas for better image quality.



HLC

Reduces bright lights and backlighting to avoid camera glare.



Anti-fog

Better visibility in bad weather: fog, snow, rain...




DIS

Ensures smooth video by gently zooming the image when the camera is subject to vibration.



ROI

Concentration of the resolution on an area of interest for face recognition by optimizing the bandwidth.



Corridor mode

90° electronic image rotation to view a larger area in a hallway.



IP66


Fully protected against dust, protected against water jets from all directions.



IK06


Fully protected against an impact of 1 joules.

Smart analysis




People detection

If someone enter this area, I am warned!




Illegal parking

If a vehicle parks in this area, I am warned!



Fence

If a vehicle or someone passes this entrance in the direction of the red arrows, I am warned!



Double fence


If a vehicle or someone passes these two bands, I am warned!

But also **add object** or **missing object**, **bad signal**, **motion detection** and **network disconnection**

The tools



Mail alert in case of intrusion



MyVizeo

An application to remotely view your cameras



Vizeo DDNS

Creation of an address accessible from the Internet